



# BOSS™ X-PO35

NON FLUSH

## Data Sheet

### General Description

A multi-purpose flushing agent.

Code: 10L Drum 16910681  
20L Drum 16910692

### Properties

- A blend of cleaning and dispersing agents
- Contains a very effective biodispersant
- Neutral formulation. Compatible with all metallic & non-metallic components generally found in closed circuit systems.

### Benefits

- Lifts & mobilises system contaminants including biofilm
- Cleans & passivates bare metal surfaces, preventing under deposit corrosion and prolonging system life
- Straightforward test method available
- This product has been formulated so that it can remain in the system after the addition of BOSS™ X-PO10 inhibitor

### Use Instructions

Normal Dose Rate: 0.36%

Instructions: Add product to the system to achieve a concentration of 0.36%.

Circulate for an optimum period of 48 hours.

For best results, a good flow rate is required.

Always use this product in conjunction with an X-Pot so that all system debris can be effectively removed.

### Technical Data

Composition: An aqueous solution of phosphonates, ethoxylate and polymers.

Appearance: Pale yellow

Sg (at 20°C): 1.06

pH: 7-9

### Product Compatibility

Compatible with most closed circuit water treatment products. This product has been

formulated specifically for use with BOSS™  
X-PO10 inhibitor.

## Handling and Storage

Avoid direct contact with the substance.  
Store in a cool, well-ventilated area.  
Keep container tightly closed.  
For full guidance on health and safety matters, consult the Safety Data Sheet (SDS).  
Carry out a 'Control of Substances Hazardous to Health' (COSHH) assessment before use.

## Test Methods

Laboratory: Test for nitrite 0.36% product gives 100ppm nitrite.

Site: Test for nitrite 0.36% product gives 100ppm nitrite.

## Emergency Contact Number

In case of emergency, please contact:  
0844 3727344