



Image not yet available

# BOSS™ X-PO40

## DE-SLUDGER

### Data Sheet

#### General Description

A revolutionary premier polymeric sludge removing agent for central heating systems, designed to both de-sludge & clean the heating system.

Code: 10L Drum 16910371

#### Properties

- A blend of cleaning & dispersing agents to de-sludge systems already in use.
- Designed to remove & disperse particulate fouling.
- Effective for iron oxide deposits, hardness derived sludges & biofilms.

#### Benefits

- Near neutral pH.
- Non-aggressive.
- High dispersing power.
- Fast-acting.

#### Use Instructions

**Normal Dose Rate:** To a typical central heating system (70L) dose 250ml. This is equivalent to 0.036% (vol/vol).

**Instructions:** Use in existing installations. Circulate for a minimum of 24 hours.

For best results, a good flow rate is required. Flush the system with clean water before filling the system & treating it with BOSS™ X-PO10 inhibitor.

If the pipework is totally blocked with debris, remove system components and jet out with water prior to flushing procedure.

#### Technical Data

**Composition:** An aqueous solution of polymers & surfactants.

**Appearance:** Colourless

**Sg (at 20°C):** 1.095

**pH:** 5 - 6

#### Product Compatibility

Compatible with all BOSS™ X-PO water treatment products.

## Handling and Storage

Avoid direct contact with the substance.

Ensure there is sufficient ventilation of the area.

Do not handle in a confined space.

Avoid the formation or spread of mist in the air.

Store in a cool, well-ventilated area.

Keep container tightly closed.

For full guidance on health and safety matters, consult the Safety Data Sheet (SDS).

Carry out a 'Control of Substances Hazardous to Health' (COSHH) assessment before use.

## Test Methods

Laboratory: No test method available.

Site: No test method available.

## Emergency Contact Number

In case of emergency, please contact:

0844 3727344