



# BOSS™ X-PO50

## MONOPROPYLENE READY MIX

### Data Sheet

Image not yet available

### General Description

A BuildCert Approved inhibitor plus Monopropylene Glycol anti-freeze. Pre-mixed formulation for chilled water circuits, including air source heat pumps to give freeze protection to -12°C.

Code: 16901862

### Properties

- Reduces the freezing point of water
- Gives protection to -12°C (if undiluted)
- Good corrosion control for most common metals of construction

### Benefits

- Ready to use
- Low toxicity
- Free from nitrites
- Free from borates

### Use Instructions

Normal Dose Rate: Dose neat  
Instructions: No dilution required

### Product Compatibility

Do not mix with other chemicals unless advised by your consultant.

### Technical Data

Composition: An aqueous solution of monopropylene glycol and corrosion inhibitors.

Appearance: Colourless

Sg (at 20°C): 1.011

pH: 6.5 - 7.5

### Handling and Storage

Store in a cool, well-ventilated area. Keep container tightly closed. For full guidance on health and safety matters, consult the Safety Data Sheet (SDS) Carry out a 'Control of Substances Hazardous to Health' (COSHH) assessment before use.

### Test Methods

Laboratory: Not applicable

Site: Not applicable

## **Emergency Contact Number**

In case of emergency, please contact:

0844 3727344