



BOSS™ X-PO60

MONOETHYLENE READY MIX

Data Sheet

Image not yet available

General Description

A BuildCert Approved inhibitor plus Monoethylene Glycol anti-freeze. Pre-mixed formulation for chilled water circuits, including ground source heat pumps to give freeze protection to -10°C.

Code: 16901884

Properties

- Reduces the freezing point of water to -10°C
- Good corrosion control for most common metals of construction

Benefits

- Ready to use
- Free from nitrites
- Free from borates

Use Instructions

Normal Dose Rate: Dose neat - no dilution required

Instructions: Not suitable for applications where a leak may potentially contaminate food

Product Compatibility

Do not mix with other chemicals unless advised by your consultant.

Technical Data

Composition: An aqueous solution of monoethylene glycol and corrosion inhibitors.
Appearance: Colourless
Sg (at 20°C): 1.033
pH: 7 - 7.5

Handling and Storage

Store in a cool, well-ventilated area. Keep container tightly closed. For full guidance on health and safety matters, consult the Safety Data Sheet (SDS). Carry out a 'Control of Substances Hazardous to Health' (COSHH) assessment before use.

Test Methods

Laboratory: Not applicable
Site: Not applicable

Emergency Contact Number

In case of emergency, please contact:
0844 3727344