

# MATERIAL SAFETY DATA SHEET FOR BOSS MS GASWELD RODS – 84651043, 1054, 1065

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Product type:	Mild Steel Gas Weld Rod	
Intended use:	Oxy-Fuel Gas Welding	
Trade Name:	BOSS MS Gasweld Rod	
Supplier of product:	The BSS Group Ltd	
Registered Office:	Travis Perkins PLC, Lodge Way House, Lodge Way, Harlestone Road, Northampton	
	NN5 7UG.	
Telephone/Fax Numbers:	0116 245 5500 / 0116 218 2214	
E-mail Address	reception@bssgroup.com	
Web site Address	www.bssindustrial.co.uk	

## 2. HAZARD IDENTIFICATION

Risk by welding use	
Heat:	Spatter and melting metal can cause burn injuries
Radiation:	UV, IR radiations. Arc spray can severely damage eyes and skin
Fumes:	Formation of dangerous fumes during use. Inhalation of welding fumes may cause respiratory irritation. Cough. Excessive or prolonged inhalation of fumes may cause metal fume fever.
Electricity:	Electric shock can kill
Magnetic Fields:	Persons with a pacemaker should not go near welding or cutting operations until they have consulted their doctor and obtained information from the manufacturer or the device.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS.

<b>Main Constituents:</b>	Value (s) %	CAS No/EC No/EC Index	Symbol (s)	R-Phrase (s)
Iron	96 to 98	7439-89-6 / 231-096-4 /		
Manganese	0.1 to 1%	7439-96-5 / 231-105-1 /		
Silicon	<0.2%	7440-21-3 / 231-130-8 /		

## 4. FIRST AID MEASURES

Eye Contact:	Rinse immediately with plenty of water. Seek medical attention immediately	
Skin Contact:	Take off immediately all contaminated clothing. Flush with plenty of water. Seek	
	medical advice	
Inhalation:	Assure fresh air breathing. Obtain medical attention if breathing difficulty persists.	
Ingestion:	Rinse mouth. Do not induce vomiting. Obtain emergency medical attention.	



## **5. FIRE FIGHTING MEASURES**

Flammable Class:	The product is not flammable	
Prevention:	Welding hot slag or sparks may cause fire	
Extinguishing Media:	Powder. Foam. Carbon dioxide	
Protection against Fire:	Do not enter fire area without proper protective equipment, including respiratory	
_	protection.	

## **6. ACCIDENTAL RELEASE MEASURES**

Personal Precautions:	Equipment cleanup crew with suitable protection
After Spillage or Leakage:	On land sweep or shovel into suitable containers

## 7. HANDLING AND STORAGE:

Storage precautions:	Store in a dry protected location to prevent moisture contact. Keep container closed when		
	not in use		
Handling:	Provide local exhaust or general room ventilation to minimise fume concentration. Wash		
	hands and other exposed areas with mild soap and water before eating, drinking or		
	smoking and when leaving work.		

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection:	In case of insufficient ventilation, wear suitable respiratory equipment. Do not breathe gas/fumes/vapour	
Eye Protection:	Use a protection mask equipped with suitable filter glass	
	Interdiction to wear contact lens	
Skin Protection:	Skin protection appropriate to the conditions of use should be provided	
Hand Protection:	Welding gloves	

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Solid
Colour:	Copper
Odour:	Odourless
Melting Point °C:	Ca. 1500

BOSS MSDS – 006 REVIEWED: 04/03/2013 Page: 2 of 4



# 10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions (<300°C)	
Materials to Avoid:	Contact with chemical substances eg. Acids which could cause generation of gas	
<b>Hazardous Decomposition</b>	Formation of dangerous fumes during use. Welding fumes are classified carcinogen by the	
Products:	IARC (International Agency for Research on Cancer): Group 2B Cancer suspect agent.	
	Reasonably expected gaseous products would include carbon oxides, nitrogen oxides &	
	ozone.	
Fume Data Sheet:	According to process conditions, hazardous decomposition may be generated. These	
	hazardous products could include those from the reaction or oxidation of the components	
	listed in section 3 or included in base material.	
Fume Emission Rate:	The amount of fumes generated change with the welding parameters and the diameters of	
	the consumable. Refer to applicable national exposure limits for fume compounds and	
	national exposure limits for fume.	
Other information:	In case of work on parts covered by coatings such as: lubricants, solvent, paint, metallic	
	compounds, grease etc. The thermal or photochemical decompositional products of these	
	elements cumulate with dust and fumes emitted by the melting of the welding product.	
	The solution to adopt must be, in any case, preceded by a spot study. Refer to the	
	document "Health & Safety in Welding" published by the International Institute of	
	Welding (IIS/IIW)	

## 11. TOXICOLOGICAL INFORMATION

<b>Toxicity Information:</b>	The material or its emissions may induce an allergic or sensitisation reaction and thereby	
	aggravate existing systemic disease	
Acute Toxicity:	Inhalation of welding fumes may cause respiratory irritation, nausea, fever, giddiness, eye	
	irritation	
Chronic Toxicity:	Overexposure to welding fumes may case: Pulmonary/bronchial disease and/or cause	
	breathing difficulty	

## 12. ECOLOGICAL INFORMATION

<b>Ecological Effects</b>	Avoid release to the environment. Do not discharge in sewers
Information:	

#### 13. DISPOSAL CONSIDERATIONS

Disposal:	Dispose in a safe manner in accordance with local/national regulations
<b>Industrial Waste Number:</b>	120113 Welding Wastes
	120101 Ferrous metallic scrap

#### **14. TRANSPORT INFORMATION**

General Information:	Not regulated	
----------------------	---------------	--

#### **15. REGULATORY INFORMATION**

Symbols:	None
Risk Phrases:	None
Safety Phrases:	None

BOSS MSDS – 006 REVIEWED: 04/03/2013 Page: 3 of 4



#### **16. OTHER INFORMATION**

Warning:	Fumes and gases emitted during welding may be dangerous. Good ventilation of the workplace required.
Directive 2002/95/CE (ROHS)	Can be used in the fabrication of electric & electronic devices
Training Advice:	Ensure that the user is aware of the potential hazards and knows what to do in the event of an accident or an emergency.

#### **DISCLAIMER**

This information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.