



Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS MULTI PURPOSE LUBRICANT **Creation Date :** 25.02.20 **Version :** 2.0
Ref.Nr.: UDS000965_3_20200225 (EN) **Replaces:** UDS000965_20180628 **Revision:** 08.07.22

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

BOSS MULTI PURPOSE LUBRICANT
Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Anti Corrosion Products

1.3. Details of the supplier of the safety data sheet

BSS Industrial
Boss Court
7 Barton Close
Grove Park
Leicester
LE19 1SJ
+44 (0)116 242 7800
enquiries@bssgroup.com

1.4. Emergency telephone number

Emergency Telephone Number - +44 (0)116 245 5500 (8:30am - 5:00pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical: Aerosols, category 1

Extremely flammable aerosol.
Pressurised container: May burst if heated.

Classification is based on test data.

Health: Specific target organ toxicity - single exposure, category 3

May cause drowsiness or dizziness.

Classification based on calculation method.

Environment: Not classified

Classification based on calculation method.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Product identifier: Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics



Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS MULTI PURPOSE LUBRICANT **Creation Date :** 25.02.20 **Version :** 2.0
Ref.Nr.: UDS000965_3_20200225 (EN) **Replaces:** UDS000965_20180628 **Revision:** 08.07.22

Hazard pictogram(s):



Signal word: Danger

Hazard statement(s): H222 : Extremely flammable aerosol.

H229 : Pressurised container: May burst if heated.

H336 : May cause drowsiness or dizziness.

Precautionary statement(s): P102 : Keep out of reach of children.

P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 : Do not spray on an open flame or other ignition source.

P251 : Do not pierce or burn, even after use.

P261 : Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 : Use only outdoors or in a well-ventilated area.

P410/412 : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501-2 : Dispose of contents/container to an authorised waste collection point.

Supplemental Hazard

information: Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

| Hazardous ingredient | Registration number | CAS-nr. EC-nr | | w/w % | Hazard Class and Category | Hazard statement | Notes |
|--|---------------------|---------------|-------------|-------|---|---------------------|-------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | 01-2119463258-33 | - | (919-857-5) | 30-60 | Flam. Liq. 3, Asp. Tox. 1, STOT SE 3 | H226,H304, H336 B,Q | |
| Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%) | 01-2119485926-20 | 68512-91-4 | 270-990-9 | 10-30 | Press. Gas, Flam. Gas 1 H280,H220 | | K,G |
| Highly refined low mineral oils/hydrocarbons | - | - | - | | Asp. Tox. 1 | H304 | |
| Hydrocarbons, C10, aromatics, | 01-2119463583-34 | - | (918-811-1) | 0-1 | STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2 | H336,H304, H411 Q | |
| Explanation notes | | | | | | | |



Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS MULTI PURPOSE LUBRICANT **Creation Date :** 25.02.20 **Version :** 2.0
Ref.Nr.: UDS000965_3_20200225 (EN) **Replaces:** UDS000965_20180628 **Revision:** 08.07.22

| |
|--|
| B : substance with national established workplace exposure limit |
| G : exempted from the obligation to register in accordance with art.2(7)of REACH Regulation No 1907/2006 |
| K : not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8) |
| Q : The CAS-no is only an indicative identifier to be used outside the EU for global inventory entries. |

SECTION 4: First aid measures

4.1. Description of first aid measures

Contact with eyes : If substance has got into eyes, immediately wash out with plenty of water If eye irritation persists: Get medical advice/attention.

Contact with skin : Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

Inhalation : IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion : If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention

4.2. Most important symptoms and effects, both acute and delayed

Inhalation : Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness

Ingestion : After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. Symptoms : sore throat, abdominal pain, nausea, vomiting

Skin contact : May cause irritation. Symptoms : redness and pain

Eye contact : May cause irritation. Symptoms : redness and pain

4.3. Indication of any immediate medical attention and special treatment needed

General Advice : If you feel unwell, seek medical advice (show the label where possible If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media

Foam, carbon dioxide or dry agent

Do not use water jet extinguishing media, due to the risk of spreading fire.

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C

Forms hazardous decomposition products

CO,CO2

5.3. Advice for firefighters



Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS MULTI PURPOSE LUBRICANT **Creation Date :** 25.02.20 **Version :** 2.0
Ref.Nr.: UDS000965_3_20200225 (EN) **Replaces:** UDS000965_20180628 **Revision:** 08.07.22

Keep container(s) exposed to fire cool, by spraying with water. In case of fire, do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources
Ensure adequate ventilation
Wear suitable protective clothing and gloves.
In case of insufficient ventilation, wear suitable respiratory equipment.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition
Take precautionary measures against static discharges
Equipment should be earthed
Use explosion-proof electrical/ventilating/lighting/.../equipment.
Use only non-sparking tools.
Do not breathe aerosols or vapours.
Ensure adequate ventilation
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
Wash thoroughly after use
Wear protective gloves/protective clothing/eye protection/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C. Keep out of reach of children.

7.3. Specific end use(s)

Anti Corrosion Products



Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS MULTI PURPOSE LUBRICANT **Creation Date :** 25.02.20 **Version :** 2.0
Ref.Nr.: UDS000965_3_20200225 (EN) **Replaces:** UDS000965_20180628 **Revision:** 08.07.22

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits :

No information available

8.2. Exposure controls

Control procedures : Ensure adequate ventilation

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

Personal protection : Take precautions to avoid contact with skin and eyes when handling the product.

It is good practice to wear gloves and to provide adequate ventilation whenever using the product.

In all cases handle and use the product in accordance with good industrial hygiene practices.

inhalation : In case of insufficient ventilation, wear suitable respiratory equipment. recommended respiratory protection: Air purifying respirator equipped with organic gas/vapor cartridge (type A)

hands and skin : Depending on amount and duration of use and the risk of contact with the product the gloves manufacturer can assist you in the selection of the right glove material and breakthrough time.

Recommended gloves: Nitrile

eyes : Wear safety eyewear according to EN 166.

Environmental protection: Avoid release to the environment.
Collect spillage.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Appearance : physical state : Propane/butane propelled liquid.

colour : Yellow.

odour : Characteristic odor.

pH : Not applicable.

Boiling point/range : 145 °C

Flash point : 41 °C (Closed Cup)

Evaporation rate : Not available.

Explosion limits : upper limit : 7.0 %

lower limit : 0.6 %

Vapour pressure : Not available.

Relative density : 0.837 g/cm³ (@ 20°C).

Solubility in water : Insoluble in water

Auto-ignition : 200 °C

Viscosity : Not available.

9.2. Other information



Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS MULTI PURPOSE LUBRICANT **Creation Date :** 25.02.20 **Version :** 2.0
Ref.Nr.: UDS000965_3_20200225 (EN) **Replaces:** UDS000965_20180628 **Revision:** 08.07.22

**VOC = volatile organic
compounds** 576 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

acute toxicity: based on available data the classification criteria are not met **skin
corrosion/irritation: based on available data the classification criteria are not met **serious eye
damage/irritation: based on available data the classification criteria are not met **respiratory or
skin******

sensitisation: based on available data the classification criteria are not met **germ cell
mutagenicity: based on available data the classification criteria are not met **carcinogenicity:**
based on available data the classification criteria are not met **toxicity for reproduction:** based
on available data the classification criteria are not met **STOT-single exposure:** May cause
drowsiness or dizziness.**

STOT repeated exposure: based on available data the classification criteria are not met
aspiration hazard: based on available data the classification criteria are not met

Information on likely routes of exposure:



Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS MULTI PURPOSE LUBRICANT **Creation Date :** 25.02.20 **Version :** 2.0
Ref.Nr.: UDS000965_3_20200225 (EN) **Replaces:** UDS000965_20180628 **Revision:** 08.07.22

Inhalation : Inhalation of solvent vapours may give rise to nausea, headaches and dizziness **Ingestion :** After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.
Skin contact : Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis
Repeated exposure may cause skin dryness or cracking.
Eye contact : May cause irritation.

Toxicological data :

| Hazardous ingredient | CAS-nr. | method | | |
|--|---------|-----------------|--------------|--|
| Hydrocarbons, C10, aromatics, | - | LD50 oral rat | > 5000 mg/kg | |
| | | LC50 inhal.rat | 4688 mg/m3 | |
| | | LD50 derm.rabit | > 2000 mg/kg | |
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | - | LD50 oral rat | >5000 mg/kg | |
| | | LC50 inhal.rat | 4951 mg/m3 | |
| | | LD50 derm.rabit | >5000 mg/kg | |

SECTION 12: Ecological information

12.1. Toxicity

Not classified

Ecotoxicological data:

| Hazardous ingredient | CAS-nr. | method | | |
|-------------------------------|---------|--------------|-----------|--|
| Hydrocarbons, C10, aromatics, | - | IC50 algae | > 10 mg/l | |
| | | LC50 fish | 2-5 mg/l | |
| | | EC50 daphnia | 3-10 mg/l | |

12.2. Persistence and degradability

No information available

12.3. Bioaccumulative potential

No information available



Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS MULTI PURPOSE LUBRICANT **Creation Date :** 25.02.20 **Version :** 2.0
Ref.Nr.: UDS000965_3_20200225 (EN) **Replaces:** UDS000965_20180628 **Revision:** 08.07.22

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

No information available

GWP (global warming potential): 1

SECTION 13: Disposal considerations

13.1. Waste treatment methods

National regulations : Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number : 1950

14.2. UN proper shipping name

Proper shipping name: AEROSOLS

14.3. Transport hazard class(es)

Class: 2.1
ADR/RID - Classification code: 5F

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

ADR/RID - Environmentally
hazardous: No
IMDG - Marine pollutant: No
IATA/ICAO - Environmentally



Safety Data Sheet
Regulation EC No 1907/2006 Art.31

Product Name: BOSS MULTI PURPOSE LUBRICANT **Creation Date :** 25.02.20 **Version :** 2.0
Ref.Nr.: UDS000965_3_20200225 (EN) **Replaces:** UDS000965_20180628 **Revision:** 08.07.22

hazardous: No

14.6. Special precautions for user

ADR/RID - Tunnelcode: (D)
IMDG - Ems: F-D, S-U
IATA/ICAO - PAX: 203
IATA/ICAO - CAO: 203

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.
Regulation (EC) No 1907/2006 (REACH)
Regulation (EC) No 1272/2008 (CLP)
Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation hazard statements: H220 : Extremely flammable gas.
H226 : Flammable liquid and vapour.
H280 : Contains gas under pressure; may explode if heated.
H304 : May be fatal if swallowed and enters airways.
H336 : May cause drowsiness or dizziness.
H411 : Toxic to aquatic life with long lasting effects.

REVISIONS IN CHAPTRE : Classification according to Regulation (EC) No 1272/2008
Labelling according to Regulation (EC) No 1272/2008

acronyms and synonyms: TWA = time weight average
STEL = short time exposure limit
VOC = volatile organic compounds
PBT = persistant bioaccumulative toxic
vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission.