



Certificate number: 2306701 (2)

Issued 13/06/2023

Expires 16/11/2027

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

BSS Industrial.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
BSS Industrial.
Cross Point Business Park
Ashcroft Way
Coventry
CV2 2TU
United Kingdom



KUKreg4

Product Certificate

Appendix to Certificate number: 2306701

The following products belong to this certificate

PRODUCT DESCRIPTION Range of in-line, lever operated spherical isolation valves with brass bodies & chrome plated balls, stainless steel wire filters and plastic flow regulators. For use with copper pipe EN1057 only. ATS3 – Without Production Surveillance.
MODEL(S) BOSS 282CF Calflow 28200011; 28200022; 28200033; 28200044; 28200055; 28200066; 28200077.
SIZE: 15mm x 15mm compression.
SCOPE: Manufacturer recommended maximum working pressure 10 Bar & Maximum operating temperature 85°C, except for models 28200066 & 28200077 with maximum operating temperature 60°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C, except for models 28200066 & 28200077 with maximum temperature 60°C.
MARKING Airaga logo on body.
MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.
BACKFLOW PROTECTION NOTES N/A.
ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.

Extra Notes